

#### Application

The 2115HT/HTi is a full-range, two-way system designed for a wide variety of speech and music applications, such as clubs, churches, or concert settings.

#### Description

The 2115HT/HTi is trapezoidal in shape, facilitating cluster or array installations. It can be utilized for permanent or portable applications.

#### Cabinetry

The cabinet design uses a 9 ply 3/4" Birch plywood with dado joints, recessed baffle and a 16 gauge front perforated grill for long lasting durability. The 2000 Series is equipped with two parallel 1/4" jacks and one Neutrik Speakon jack.

#### Covering Options

The cabinet is covered by high grade Ozite using waterproof adhesive. It is also available in black or white Duracoat and natural birch finish. \*\*

#### Transducers

The two-way cabinet is loaded with a 15" low frequency driver and a 1" Titanium compression driver(HTi)\*\* or a 1" screw on Motorola Powerline(HT). The high frequency driver is coupled with a durable ABS horn for proper dispersion. The cabinet is tuned by means of a vented port set at the optimum frequency.

\*\*Refer to price sheet for upgrade pricing.

#### Specifications

<b>Frequency Response:</b>	50hz-18Khz
<b>Power Handling:</b>	350w (cont.)
<b>Sensitivity (1 watt/meter):</b>	100dB
<b>Nominal Dispersion:</b>	40v x110h
<b>Impedance:</b>	8 Ohms
<b>Transducer Components</b>	
Low Frequency:	15" woofer
High Frequency:	1" Powerline (HT) or 1" titanium (HTi)
<b>Audio Input Connections:</b>	2 - 1/4" & 1 - Speakon jack
<b>Enclosure:</b>	Vented
<b>Crossover:</b>	LR
<b>High Frequency Protection:</b>	Yes
<b>Steel Pole Mount:</b>	Yes
<b>Physical</b>	
Dimensions (H x W x D):	29.5" x 21" x 18" (74.9cm x 53.3cm x 47.8cm)
HT Weight:	62 lbs./28.2 Kg
HTi Weight:	67 lbs./30.5 Kg

#### Warranty Information

The 2000 Series high definition speakers feature a 10 year warranty. Please refer to the warranty information card shipped with all Sound Bridge speaker products.

