

Application

The 2212HT is a full-range, two-way system designed for a wide variety of speech and music applications, such as clubs, churches, or concert settings.

Description

The 2212HT is trapezoidal in shape, facilitating cluster or array installations. It can be utilized for permanent or portable applications.

Cabinetry

The cabinet design uses a 9 ply 3/4" Birch plywood with dado joints, recessed baffle and a 16 gauge front perforated grill for long lasting durability. The 2000 Series is equipped with two parallel 1/4" jacks and one Neutrik Speakon jack.

Covering Options

The cabinet is covered by high grade Ozite using waterproof adhesive. It is also available in black or white Duracoat and natural birch finish. **

Transducers

The two-way cabinet is loaded with two 12" low frequency driver and a 1" Titanium high frequency compression driver. The high frequency driver is coupled with a durable ABS horn for proper dispersion. The cabinet is tuned by means of a vented port set at the optimum frequency.

**Refer to price sheet for upgrade pricing.

Specifications

Frequency Response:	45hz-18Khz
Power Handling:	400w (cont.)
Sensitivity (1 watt/meter):	96dB
Nominal Dispersion:	70v x110h
Impedance:	4 Ohms
Transducer Components	
Low Frequency:	12" woofer (2)
High Frequency:	1" titanium
Audio Input Connections:	2 - 1/4" & 1 - Speakon jack
Enclosure:	Vented
Crossover:	LR
High Frequency Protection:	Yes
Steel Pole Mount:	No
Physical	
Dimensions (H x W x D):	37" x 19.8" x 19" (94cm x 50.3cm x 48.3cm)
HT Weight:	73 lbs./33.2 Kg

Warranty Information

The 2000 Series high definition speakers feature a 10 year warranty. Please refer to the warranty information card shipped with all Sound Bridge speaker products.

