

Application

The 2215HT is a full-range, two-way system designed for a wide variety of speech and music applications, such as clubs, churches, or concert settings.

Description

The 2215HT is trapezoidal in shape, facilitating cluster or array installations. It can be utilized for permanent or portable applications.

Cabinetry

The cabinet design uses a 9 ply 3/4" Birch plywood with dado joints, recessed baffle and a 16 gauge front perforated grill for long lasting durability. The 2000 Series is equipped with two parallel 1/4" jacks and one Neutrik Speakon jack.

Covering Options

The cabinet is covered by high grade Ozite using waterproof adhesive. It is also available in black or white Duracoat and natural birch finish. **

Transducers

The two-way cabinet is loaded with two 15" low frequency driver and a 1" Titanium high frequency compression driver. The high frequency driver is coupled with a durable ABS horn for proper dispersion. The cabinet is tuned by means of a vented port set at the optimum frequency.

**Refer to price sheet for upgrade pricing.

Specifications

| | |
|------------------------------------|--|
| Frequency Response: | 40hz-18Khz |
| Power Handling: | 450w (cont.) |
| Sensitivity (1 watt/meter): | 96dB |
| Nominal Dispersion: | 60v x110h |
| Impedance: | 4 Ohms |
| Transducer Components | |
| Low Frequency: | 15" woofer (2) |
| High Frequency: | 1" titanium |
| Audio Input Connections: | 2 - 1/4" & 1 - Speakon jack |
| Enclosure: | Vented |
| Crossover: | LR |
| High Frequency Protection: | Yes |
| Steel Pole Mount: | No |
| Physical | |
| Dimensions (H x W x D): | 47" x 18.5" x 20.5" (119cm x 47cm x 52.1cm) |
| HT Weight: | 84 lbs./38.2 Kg |

Warranty Information

The 2000 Series high definition speakers feature a 10 year warranty. Please refer to the warranty information card shipped with all Sound Bridge speaker products.

