

Application

The 2218SWR is an extended low-range system designed for a wide variety of speech and music applications, such as clubs, churches, or concert settings.

Description

The 2218SWR is rectangular in shape. It is designed to be utilized as a low frequency enhancement to the 2000 series full-range speakers. It can be used for permanent or portable applications.

Cabinetry

The cabinet design uses a 9 ply 3/4" Birch plywood with dado joints, recessed baffle and a 16 gauge front perforated grill for long lasting durability. The 2000 Series is equipped with two parallel 1/4" jacks and one Neutrik Speakon jack.

Covering Options

The cabinet is covered by high grade Ozite using waterproof adhesive. It is also available in black or white Duracoat and natural birch finish. **


Transducers

The cabinet is loaded with two 18" low frequency drivers in a tuned enclosure. The cabinet is tuned by means of a vented port set at the optimum frequency.

**Refer to price sheet for upgrade pricing.

Specifications

Frequency Response:	35hz-500hz
Power Handling:	800w (cont.)
Sensitivity (1 watt/meter):	99dB
Nominal Dispersion:	N/A
Impedance:	4 Ohms
Transducer Components	
Low Frequency:	2 -18" woofers
High Frequency:	None
Audio Input Connections:	2 - 1/4" & 1 - Speakon jack
Enclosure:	Vented
Crossover:	No
High Frequency Protection:	N/A
Steel Pole Mount:	Yes
Physical	
Dimensions (H x W x D):	46" x 24" x 26" (116.8cm x 61cm x 66cm)
Weight:	129.5lbs./58.9 Kg



Warranty Information

The 2000 Series high definition speakers feature a 10 year warranty. Please refer to the warranty information card shipped with all Sound Bridge speaker products.