

# **Model SB2118SW**

Sub-Woofer

## Application

The 2118SW is an extended low-range system designed for a wide variety of speech and music applications, such as clubs, churches, or concert settings.

#### Description

The 2118SW is trapezoidal in shape, facilitating cluster or hidden application. It is designed to be utilized as a low frequency enhancement to the 2000 series full-range speakers. It can be used for permanent or portable applications.

#### Cabinetry

The cabinet design uses a 9 ply 3/4" Birch plywood with dado joints, recessed baffle and a 16 gauge front perforated grill for long lasting durability. The 2000 Series is equipped with two parallel 1/4" jacks and one Neutrik Speakon jack.

#### **Covering Options**

The cabinet is covered by high grade Ozite using waterproof adhesive. It is also available in black or white Duracoat and natural birch finish. \*\*

#### Transducers

The cabinet is loaded with a 18" low frequency driver in a tuned enclosure. The cabinet is tuned by means of a vented port set at the optimum frequency.

\*\*Refer to price sheet for upgrade pricing.


### Specifications

opouliourion in	
Frequency Response:	35hz-600hz
Power Handling:	350w (cont.)
Sensitivity (1 watt/meter):	99dB
Nominal Dispersion:	N/A
Impedance:	8 Ohms
Transducer Components	
Low Frequency:	18" woofer
High Frequency:	None
Audio Input Connections: 2 - 1/	4" & 1 - Speakon jack
Enclosure:	Vented
Crossover:	No
High Frequency Protection:	N/A
Steel Pole Mount:	Yes
Physical	
Dimensions (H x W x D):	24" x 24.8" x 32"
	61cm x 63cm x 81.3cm)
Weight:	68lbs./31 Kg

#### **Warranty Information**

The 2000 Series high definition speakers feature a 10 year warranty. Please refer to the warranty information card shipped with all Sound Bridge speaker products.







3501 Interstate 35E • Waxahachie, TX 75165 • 800 628-9084 • FAX (972) 935-0539