



SLICE™

SERIES-7000

APPLICATIONS:

- ▶ - LIVE/CONCERT SOUND
- ▶ - HOUSES OF WORSHIP
- ▶ - TOURING SOUND COMPANIES
- ▶ - THEATERS/LIVE VENUES
- ▶ - CORPORATE RENTAL HOUSES

DESCRIPTION:

SLICE™ = Performance

Designed for the concert sound industry and the high-end installation market where extremely high output and sonic precision are critical, the SLICE™ Series of high-performance stage monitors stand above the pack.

Loud, Light, Low-Profile

By delivering a powerful 138dB SPL peak output, while weighing in at only 56 pounds and standing 14.5" tall, the 7125WX is at the top of its class with regards to output versus size/weight.

Crisp Highs, Clean Mids

A key feature of the SLICE™ series is the use of a 2" Neodymium Mid/HF EXO driver. One driver, which excels at eliminating crossover and phase/time anomalies, reproduces all frequencies from critical vocal intelligibility range up through upper-harmonics and to top of the frequency band. This results in a clean, pure vocal and upper-mid response that sounds more natural than the traditional "PA sound" and cuts through better on a loud stage. Mixes never sound "crowded" or "muddy".

Strong Lows

The 7125WX utilizes a high-output, high-efficiency neodymium 15" low-frequency driver. Loaded in the solid 13-ply birch cabinet, the system is tuned to provide LF extension below 40Hz.

Roadworthy

SLICE™ Series stage monitors are finished in 100% solid tour-grade Duracoat™. This surface is highly abrasion resistant for rigorous touring applications.

Units are wired for Biamp operation. Recommended amp and cabling configurations are available, as well as DSP processor settings for many commonly used system controllers.

SPECIFICATIONS:

Horizontal Dispersion: Asymmetrical, 90-degrees near-field, narrowing to 50-degrees at 3m

Vertical Dispersion: 40-degrees

Frequency Response: 38Hz -to- 18kHz, +/-3dB

Max SPL: 132dB SPL Cont., 138dB SPL Peak

LF Drive Unit(s): (1) Neodymium 15" Cone

LF Sensitivity: 102dB 1w/1m

LF Power Handling: 1000w (AES), 4000w (Peak)

LF Impedance: 8-Ohms

HF Drive Unit(s): (1) Neodymium MF/HF EXO

HF Sensitivity: 118dB 1w/1m

HF Power Handling: 250w (AES), 1000w (Peak)

HF Impedance: 16-Ohms

Cabinet Construction: 18mm 13-Ply Baltic Birch, High Tensile UHMW Composite

Cabinet Finish: Tour-Grade Duracoat™

Connections: (2) Neutrik NL-4 Speakon

Dimensions (Imperial): 14.5" x 28.75" x 20.5"

Dimensions (Metric): 36.8cm x 73cm x 52.1cm

Weight: 56lbs (25.4kgs)

Accessories: HP-7125 Road Case (holds 2 units), FP-7125 Road Case (holds 4 units)