



## DESCRIPTION:

The 7218SWX is a high-performance, high-output subwoofer system designed to compliment XYON™ line array systems in a variety of permanently-installed and live sound reinforcement applications. The 7218SWX utilizes advanced components and technology to attain the highest performance levels.

7218SWX units are configured as alternating upright and inverted units, paired to create a low-frequency horn termed QUAD-One™. By focusing all four LF drivers at the same quadrant of a sphere, greater directivity and increased sensitivity is realized. Whereas typical line array systems require very large arrays to achieve this level of directivity and output, XYON™ does so with as few as two elements.

The standard 7218SWX is intended for ground-stack only applications. It includes heavy-duty casters, and single-box padded transport covers are available.

The 7218SWX-F version is intended for flown applications and includes the integrated XYON™ Z-MAX modular rigging system. 7218SWX-F enclosures may be transported in two's or four's on DL-7218 Dolly Boards, and padded transports covers are available.

Recommended amp and cabling configurations are available, as well as DSP processor settings for many commonly used system controllers.

The 7218SWX is the perfect companion subwoofers for XYON™ line array systems, such as the 7108XY, the 7208XF, the 7222XY, and the 7225XF.

## APPLICATIONS:

- ▶ - HOUSES OF WORSHIP
- ▶ - TOURING SOUND COMPANIES
- ▶ - LIVE/CONCERT SOUND
- ▶ - CORPORATE RENTAL HOUSES
- ▶ - THEATERS/LIVE VENUES
- ▶ - CLUBS/LOUNGES

## SPECIFICATIONS:

**Frequency Response:** 38Hz -to- 200Hz, +/-3dB

**Max SPL:** 144dB SPL (1 unit), 156dB SPL (4 units)

**LF Drive Unit(s):** (2) Neodymium 18" Cone

**LF: Sensitivity:** 105dB 1w/1m

**LF Power Handling:** 2000w (AES), 8000w (Peak)

**LF Impedance:** 4-Ohms

**Cabinet Construction:** 18mm 13-Ply Baltic Birch, High Tensile UHMW Composite

**Cabinet Finish:** Tour-Grade Duracoat™

**Hardware:** XYON Z-MAX Modular Rigging System

**Connections:** (2) Neutrik NL-4 Speakon

**Dimensions (Imperial):** 19" x 38.75" x 26.25"

**Dimensions (Metric):** 48.3cm x 98.4cm x 66.7cm

**Weight:** 192lbs (87.1kgs)

**Available Accessories:** FB-7208/7218L Fly Bar, DL-7218 Dolly Board (up to 4 units), CV2-7218 Padded Transport Cover (2 units on dolly)



Low Frequency Modules