SOUND-BRIDGE Acoustic Labs

Model SB3118SW

Sub-Woofer

Application

The 3118SW is an extended low-range system designed for a wide variety of speech and music applications, such as clubs, churches, or concert settings.

Description

The 3118SW is trapezoidal in shape with a curved front, facilitating cluster or stacked applications. It is designed to be utilized as a low frequency enhancement to the 3000 series full-range speakers.

Cabinetry

The cabinet design uses a 13 ply 3/4 high quality baltic birch plywood with dado joints, recessed baffle and a 16 gauge front perforated grill for long lasting durability. The baffle is cut from 1" MDF to enhance acoustical properties and to give the components a rigid interface. Two Neutrik Speakon connectors and Neutrik parallel 1/4" jacks are installed on all speakers in the 3000 series.

Covering Options

The cabinet comes coated in black Duracoat. It is also available in white Duracoat and a natural birch finish. Please refer to price sheet for upgrade pricing.

Transducers

The cabinet is loaded with a 18" cast aluminum low frequency driver in a tuned vented enclosure. The cabinet is tuned by means of a vented port set at the optimum frequency.

Specifications		
Frequency Response:	35hz-800	hz
Power Handling:	450w (coi	nt.)
Sensitivity (1 watt/meter):	99dB	
Nominal Dispersion:	N/A	
Impedance:	8 Ohms	
Transducer Components		
Low Frequency:	18" woofe	r
High Frequency:	None	
High Frequency: Audio Input Connections: Two Net		ectors
		ectors
Audio Input Connections: Two Net		ectors
Audio Input Connections: Two Net and two parallel jacks.	utrik Speakon conn	ectors
Audio Input Connections: Two Net and two parallel jacks. Enclosure:	utrik Speakon conn Vented	ectors
Audio Input Connections: Two Net and two parallel jacks. Enclosure: Crossover:	utrik Speakon conn Vented None	
Audio Input Connections: Two Net and two parallel jacks. Enclosure: Crossover: High Frequency Protection:	utrik Speakon conn Vented None N/A	
Audio Input Connections: Two Net and two parallel jacks. Enclosure: Crossover: High Frequency Protection: Steel Pole Mount:	utrik Speakon conn Vented None N/A	rted
Audio Input Connections: Two Net and two parallel jacks. Enclosure: Crossover: High Frequency Protection: Steel Pole Mount: Physical	utrik Speakon conn Vented None N/A Yes, Inver	rted


Warranty Information

The 3000 Series high definition speakers feature a 10 year warranty. Please refer to the warranty information card shipped with all Sound Bridge speaker products.

3501 Interstate 35E • Waxahachie, TX 75165 • 800 628-9084 • FAX (972) 935-0539

Sound Bridge Acoustic Labs is dedicated to excellence. Therefore, we retain the right to improve design, materials and workmanship. (Or in legal jargon: Prices and Specifications are subject to change without notice.)







Acoustic



